


## Valvola a sfera 3 vie Inox Sabbiata

### 3 way Ball valve Stainless steel threaded sandblasted

 <p>Pneumatic DA <b>D460/1</b></p>	 <p>Electric <b>E460/1</b></p>	 <p>Hand level <b>H460/1</b></p>	 <p>Valve only <b>V460/1</b></p>
<p>Attuate pneumaticamente / Pneumatic Actuated</p>	<p>Attuate elettricamente / Electric Actuated</p>	<p>Manuale / Hand Level</p>	<p>Corpo Valvola / Only Valve</p>

<p>Valvola a sfera a 2 vie filettata sabbiata Filetto ISO228 femmina-femmina, passaggio ridotto Interfaccia: ISO5211-DIN 3337 Connessione: Filettata ISO228 Lunghezza: Non unificato Passaggio: Ridotto Corpo: Acciaio inox AISI304L o AISI316L Sfera: Acciaio inox AISI304L o AISI316L Misure: 1/2" bis 2 1/2" Guarnizioni: PTFE, Viton (altri su richiesta) Temperatura: -20°C a +160°C Su richiesta:</p> <ul style="list-style-type: none"> <li>• Fletto ISO 7</li> <li>• Filetto NPT</li> <li>• PTFE caricato vetro oppure carbografite</li> <li>• Polietilene ad alta densità</li> <li>• ATEX II 2GD T4</li> </ul>	<p>2-ways threaded ball valve sandblasted type Thread ISO228 female-female, reduced bore Interface : ISO5211-DIN 3337 Connection Threaded ISO228 Length: Not standardized Bore Reduced Body Stainless steel AISI304L or AISI316L Ball: Stainless steel AISI304L or AISI316L Size: 1/2" bis 2 1/2" Seals , Viton (others on request) : PTFE Temperatur : -20°C +1 0°C e to 6 On request:</p> <ul style="list-style-type: none"> <li>• Threaded ISO 7</li> <li>• Threaded NPT</li> <li>• PTFE with glass or carbographe</li> <li>• Polyethylene high molecular weight</li> <li>• ATEX II 2GD T4</li> </ul>
---	--

### Rometec srl

Via Alessandro Minuziano, 87 – 89

00128 – Roma

Email: [info@rometec.it](mailto:info@rometec.it)

Tel 06-5061635 / Fax 06-5061542

