




Automation
Center
Germany



Valvola a sfera Inox ATEX

 <p>Pneumatic DA D413A4</p>	 <p>Electric E413A4</p>	 <p>Hand lever H413A4</p>	 <p>Valve only V413A4</p>
Attuate pneumaticamente	Attuate elettricamente	Manuale	Senza

<p>Valvola a sfera 2vie alta pressione con basetta ISO Filetto ISO228 femmina-femmina Interfaccia: ISO5211-DIN 3337 Connessione: Filettata ISO228 Lunghezza: Non unificato Passaggio: Ridotto Corpo: Acciaio inox AISI316L satinato Sfera: Acciaio inox AISI316L satinato Misure: 1/4" a 1" Guarnizioni: Devlon, Viton Temperatura: -20°C a +125°C Su richiesta:</p> <ul style="list-style-type: none"> • Filetto NPT • Filetto ISO7 	<p>2-ways high pressure ball valve with ISO topflange Thread ISO228 female-female Interface: ISO5211-DIN 3337 Connection: Threaded ISO228 Length: Not standardized Bore: Reduced Body: Stainless steel AISI316L glazed Ball: Stainless steel AISI316L glazed Size: 1/4" to 1" Seals: Devlon, Viton Temperature: -20°C to +125°C On request:</p> <ul style="list-style-type: none"> • Thread NPT • Thread ISO7
--	---

Rometec srl

Via Alessandro Minuziano, 87 – 89

00128 – Roma

Mail: tec@rometec.it

Tel 06-5061635 / Fax 06-5061542

ATEX II 2GD T4

