



Since 1985

LINED DOUBLE WINDOW SIGHT GLASS



Application:

- | | |
|-----------------------|-------------------------|
| 1. Food and Dairy | 6. Pulp and paper |
| 2. Marine industry | 7. Petroleum / Refinery |
| 3. Process equipment | 8. Chemical process |
| 4. Electric utilities | 9. Fertilizer |
| 5. Pharmaceuticals | 10. Steel |

Specification:

Design Standard

Flange To Flange Distance
End Connection

Manufacturing Size Range
Pressure Rating of Valve

:ASME B 16.34

:As Per ASME B 16.10 / DIN EN 558-I

:Flanged End to ASME B 16.5,150#

:BS 10 Table D / E / F / H

:PN 6 / PN 10 / PN 16

:DIN/ JIS/ IS Standard

:1" (DN25) to 6" (DN 150)

:150# / PN10 / Pn16

- Designed to observe flow of corrosive media
- High Visibility hence Easy and Quick Inspection
- Suitable upto 200 deg.C (PFA lined Sight Glass)
- Easy replacement of glass without dis-mantling complete sight glass
- Toughened Borsilicate Glass
- Durable construction / Manufactured to the highest standard
- Tailor made design (Make to order face to face dimension)
- No rotating parts-No maintenance
- All wetted parts are of PTFE and Toughened Glass

**PTFE Lined Tubular /
Full View Sight Glass**



Sizes available from 25NB to 300NB

Our Other Products:



High Pressure Bellow



Lined ball Valve

www.ablazeglassworks.com



Ashita Goel
Sales & Marketing Dept.
Ablaze Polymer, Lining & Coating Pvt. Ltd.