Rometec srl - www.rometec.it - Rometec srl - www.rometec.it - Rometec srl - www.rometec.it

## Others UDV Series

### Characteristics

This is a main model among our non-diaphragm valves. It is a 2 mm orifice-size class valve and both types of a moulded plastic body and a stainless steel body are available. *This is a solenoid-driven valve.

### Specifications

| | | |
|---|---|---|
| **Method** | Solenoid | |
| **Supply** | | |
| **Orifice （mm）** | 2 | |
| **Type** | 2way-NC | |
| **IN port pressure** | 0～600 kPa | You can choose the pressure unit. kPa |
| **OUT port pressure (NC)** | 0～50 kPa | |
| **OUT port pressure (NC)(NO)** | -～- kPa | |
| **Port connection** | M6, 1/4-28UNF | |
| **Body material** | PPS | |
| **Seal material** | FPM | |
| **Other wetted materials** | K-M31,SUS316WPA,etc. | |
| **Power consumption** | 2.4W | |
| **Operating duration** | Continuous | |
| **Outer dimensions** | 25.0 x 22.0 x 52.2 mm | |
| **Fluid temparature range** | 5～60℃ | |
| **Ambient temparature range** | 5 ～ 60 ℃ | |

Rometec srl - www.rometec.it - Rometec srl - www.rometec.it - Rometec srl - www.rometec.it