RLP-S and URA-S Sanitary Fitting Metal Bursting Discs

The ZOOK RLP-S and URA-S Sanitary Tri Clamp Fitting Bursting discs are ideal for Sanitary Applications in the Food Processing, Dairy, Brewery, Pharmaceutical, Distilling, Baking, Canning, Cosmetics and Biotechnology Industries

Features

- Fits standard Tri Clamp and NA sanitary fittings (pipework ferrules to BS 4825, please consult ZOOK Europe Ltd for compatibility with other sanitary pipework systems)
- Disc fitted with Viton sanitary fitting gaskets as standard. Buna, PTFE, EPDM and other materials also available
- Low burst pressures achieved with unique scoreless design
- No scoring of dome means high dome integrity and high cycle life compared to scored designs
- Resistant to product buildup, smooth unscored convex side of dome is presented to process medium
- Non fragmenting design
- Operates up to 90% of the disc minimum rated burst pressure
- Wide range of standard and exotic materials available
- Additional TFE corrosion protection linings available (RLP-S-L, URA-S-L)
- May be used in liquid or gas applications
- Available with burst detection options (consult ZOOK Europe Ltd)
- Three dimensional stainless steel disc tag with full disc specification permanently engraved



ZOOK Sanitary disc installed in NA Style Connector



| Burst pressure range | | | | | |
|----------------------|--------|------|---|--|--|
| Disc Nominal Size | | barç | barg @ 22º C | | |
| | | min | max | | |
| 25 mm | (1") | 1.40 | To maximum of sanitary pipework | | |
| 40 mm | (1 _") | 0.70 | | | |
| 50 mm | (2") | 0.65 | | | |
| 80 mm | (3") | 0.50 | | | |
| 100 mm | (4") | 0.40 | | | |

| Total Performance Burst Tolerance Table | | | | | | |
|---|--------|-----------------------------------|--------------|---------|--|--|
| Burst Pressure | | Total Performance Burst Tolerance | | | | |
| barg | | Standard | Intermediate | Premium | | |
| 0.14 | - 0.27 | ±35% | ±32.5% | ±30% | | |
| 0.28 | - 1.16 | ±20% | ±17.5% | ±15% | | |
| 1.17 | - 2.75 | ±15% | ±12.5% | ±10% | | |
| 2.76 | - max | ±10% | ±7.5% | ±5% | | |



Tel 0044 (0) 1909 560999

C.11 - ROMETEC STI - WWW.rometec.it - Romete@x5044 (0)/7909/6608001etec.it

Unit 33 Dinnington Business Centre