Rometec srl - www.rometec.it - info@rometec.it - Rometec srl - www.rometec.it - info@rometec.it

Carbon steel A105N - TRIM 5

NEW

2014/68/EU Directive - Risk category II / module H - NACE MR0175 & MR0103 - A105N carbon steel body & bonnet - TRIM 5 - A105N + Stellite® seat - A410 + Stellite® shutter - A410 stem - Bolted bonnet & gland pack - Rising stem for gate & globe valves - TS: -29°C/+425°C.

NACE MR0175 | NACE MR0103 | CE | 3.1 | Compatible ATEX ZONE no source of ignition



Gate valve - 150 lbs

VCA150 - RF ANSI 150
PS: 20 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VC15A150RF	VC20A150RF	VC25A150RF	VC32A150RF	VC40A150RF	VC50A150RF



Globe valve - 150 lbs

VGA150 - RF ANSI 150
PS: 20 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VG15A150RF	VG20A150RF	VG25A150RF	VG32A150RF	VG40A150RF	VG50A150RF



Gate valve - 300 lbs

VCA300 - RF ANSI 300
PS: 50 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VC15A300RF	VC20A300RF	VC25A300RF	VC32A300RF	VC40A300RF	VC50A300RF



Globe valve - 300 lbs

VGA300 - RF ANSI 300
PS: 50 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VG15A300RF	VG20A300RF	VG25A300RF	VG32A300RF	VG40A300RF	VG50A300RF



Gate valves - 800 lbs

VCA800 - Welding (SW) - Threaded (NPT)
PS: 136 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VC15A800SW	VC20A800SW	VC25A800SW	VC32A800SW	VC40A800SW	VC50A800SW
NPT code	VC15A800NPT	VC20A800NPT	VC25A800NPT	VC32A800NPT	VC40A800NPT	VC50A800NPT



Globe valves - 800 lbs

VGA800 - Welding (SW) - Threaded (NPT)
PS: 136 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VG15A800SW	VG20A800SW	VG25A800SW	VG32A800SW	VG40A800SW	VG50A800SW
NPT code	VG15A800NPT	VG20A800NPT	VG25A800NPT	VG32A800NPT	VG40A800NPT	VG50A800NPT



Piston check valves - 800 lbs

VRA800 - Welding (SW) - Threaded (NPT)
PS: 136 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VR15A800SW	VR20A800SW	VR25A800SW	VR32A800SW	VR40A800SW	VR50A800SW
NPT code	VR15A800NPT	VR20A800NPT	VR25A800NPT	VR32A800NPT	VR40A800NPT	VR50A800NPT

Rometec srl - www.rometec.it - info@rometec.it - Rometec srl - www.rometec.it - info@rometec.it

Rometec srl - www.rometec.it - info@rometec.it - Rometec srl - www.rometec.it - info@rometec.it

Stainless steel F316L - TRIM 12

NEW

2014/68/EU Directive - Risk category II / module H - NACE MR0175 & MR0103 - F316L stainless steel body & bonnet - TRIM 12 - F316L + Stellite® seat - F316 shutter - F316 stem - Bolted bonnet & gland pack - Rising stem for gate & globe valves - TS: -50°C/+450°C.

NACE MR0175 | NACE MR0103 | CE | 3.1 | Compatible ATEX ZONE no source of ignition



Gate valve - 150 lbs

VCI150 - RF ANSI 150
PS: 16 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VC15I150RF	VC20I150RF	VC25I150RF	VC32I150RF	VC40I150RF	VC50I150RF



Globe valve - 150 lbs

VGI150 - RF ANSI 150
PS: 16 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VG15I150RF	VG20I150RF	VG25I150RF	VG32I150RF	VG40I150RF	VG50I150RF



Gate valve - 300 lbs

VCI300 - RF ANSI 300
PS: 42 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VC15I300RF	VC20I300RF	VC25I300RF	VC32I300RF	VC40I300RF	VC50I300RF



Globe valve - 300 lbs

VGI300 - RF ANSI 300
PS: 42 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
code	VG15I300RF	VG20I300RF	VG25I300RF	VG32I300RF	VG40I300RF	VG50I300RF



Gate valves - 800 lbs

VCI800 - Welding (SW) - Threaded (NPT)
PS: 110 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VC15I800SW	VC20I800SW	VC25I800SW	VC32I800SW	VC40I800SW	VC50I800SW
NPT code	VC15I800NPT	VC20I800NPT	VC25I800NPT	VC32I800NPT	VC40I800NPT	VC50I800NPT



Globe valves - 800 lbs

VGI800 - Welding (SW) - Threaded (NPT)
PS: 110 bar.

NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VG15I800SW	VG20I800SW	VG25I800SW	VG32I800SW	VG40I800SW	VG50I800SW
NPT code	VG15I800NPT	VG20I800NPT	VG25I800NPT	VG32I800NPT	VG40I800NPT	VG50I800NPT

Piston check valves - 800 lbs

VRI800 - Welding (SW) - Threaded (NPT)
PS: 110 bar.



NPS	1/2"	3/4"	1"	1"1/4	1"1/2	2"
SW code	VR15I800SW	VR20I800SW	VR25I800SW	VR32I800SW	VR40I800SW	VR50I800SW
NPT code	VR15I800NPT	VR20I800NPT	VR25I800NPT	VR32I800NPT	VR40I800NPT	VR50I800NPT

Rometec srl - www.rometec.it - info@rometec.it - Rometec srl - www.rometec.it - info@rometec.it