

Cam-lock couplings

■ Brass



Individual packing

Excluded from 2014/68/EU Directive (art. 4, §3) - MIL-C-27487 & A-A-59326 - For all common fluids - Brass body - Brass cams - NBR gasket (for coupling) - PS: see table below - TS: -10°C/+80°C.

Max. allowable pressure

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
bar	11	16	16	16	16	16	11	9	7



2261 - Female adaptor A

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2261004	2261005	2261006	2261007	2261008	2261009	2261010	2261011	2261012



2262 - Male coupling B

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2262004	2262005	2262006	2262007	2262008	2262009	2262010	2262011	2262012



2263 - Hose coupling C

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2263004	2263005	2263006	2263007	2263008	2263009	2263010	2263011	2263012



2264 - Female coupling D

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2264004	2264005	2264006	2264007	2264008	2264009	2264010	2264011	2264012



2265 - Hose adaptor E

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2265004	2265005	2265006	2265007	2265008	2265009	2265010	2265011	2265012



2266 - Male adaptor F

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2266004	2266005	2266006	2266007	2266008	2266009	2266010	2266011	2266012



2267 - Cap coupling DC

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2267004	2267005	2267006	2267007	2267008	2267009	2267010	2267011	2267012



2268 - Plug adaptor DP

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2268004	2268005	2268006	2268007	2268008	2268009	2268010	2268011	2268012

■ Spare gaskets for cam-lock couplings B, C, D & DC

(brass, aluminium or stainless steel)

EPDM

NBR

FKM

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	9830850	9830851	9830852	9830853	9830854	9830855	9830856	9830857	9830858
code	9830860	9830861	9830862	9830863	9830864	9830865	9830866	9830867	9830868
code	9830870	9830871	9830872	9830873	9830874	9830875	9830876	9830877	9830878

■ Aluminium



**Individual
packing**

Excluded from 2014/68/EU Directive (art. 4, §3) - MIL-C-27487 & A-A-59326 - For all common fluids - Aluminium body - Brass cams - NBR gasket (for coupling) - PS: see table below - TS: -10°C/+80°C.

Max. allowable pressure

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
bar	11	16	16	16	16	16	11	9	7

2201 - Female adaptor A



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2201004	2201005	2201006	2201007	2201008	2201009	2201010	2201011	2201012

2202 - Male coupling B



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2202004	2202005	2202006	2202007	2202008	2202009	2202010	2202011	2202012

2203 - Hose coupling C



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2203004	2203005	2203006	2203007	2203008	2203009	2203010	2203011	2203012

2204 - Female coupling D



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2204004	2204005	2204006	2204007	2204008	2204009	2204010	2204011	2204012

2205 - Hose adaptor E



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2205004	2205005	2205006	2205007	2205008	2205009	2205010	2205011	2205012

2206 - Male adaptor F



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2206004	2206005	2206006	2206007	2206008	2206009	2206010	2206011	2206012

2207 - Cap coupling DC



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2207004	2207005	2207006	2207007	2207008	2207009	2207010	2207011	2207012

2208 - Plug adaptor DP



Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2208004	2208005	2208006	2208007	2208008	2208009	2208010	2208011	2208012

Stainless steel CF8M

**Individual
packing**

Excluded from 2014/68/EU Directive (art. 4, §3) - MIL-C-27487 & A-A-59326 - For all common fluids - Stainless steel CF8M body & cams - NBR gasket (for coupling) - PS: see table below - TS: -10°C/+80°C.

Max. allowable pressure

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
bar	11	18	18	18	18	18	16	14	14

2241 - Female adaptor A

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2241004	2241005	2241006	2241007	2241008	2241009	2241010	2241011	2241012

2242 - Male coupling B

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2242004	2242005	2242006	2242007	2242008	2242009	2242010	2242011	2242012

2243 - Hose coupling C

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2243004	2243005	2243006	2243007	2243008	2243009	2243010	2243011	2243012

2244 - Female coupling D

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2244004	2244005	2244006	2244007	2244008	2244009	2244010	2244011	2244012

2245 - Hose adaptor E

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2245004	2245005	2245006	2245007	2245008	2245009	2245010	2245011	2245012

2246 - Male adaptor F

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2246004	2246005	2246006	2246007	2246008	2246009	2246010	2246011	2246012

2247 - Cap coupling DC

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2247004	2247005	2247006	2247007	2247008	2247009	2247010	2247011	2247012

2248 - Cap adaptor DP

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	2248004	2248005	2248006	2248007	2248008	2248009	2248010	2248011	2248012

Stainless steel 316

Excluded from 2014/68/EU Directive (art. 4, §3) - MIL-A-59326 - EN 14420-7 - For all common fluids - Stainless steel 316 body - Stainless steel 304 cams - NBR gasket (for coupling) - PS: see table above - TS: -10°C/+80°C.

RCABW - Welding adaptor

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	RCABW15	RCABW20	RCABW25	RCABW32	RCABW40	RCABW50	RCABW65	RCABW80	RCABW100

RCCBW - Welding coupling

Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	2"1/2	3"	4"
code	RCCBW15	RCCBW20	RCCBW25	RCCBW32	RCCBW40	RCCBW50	RCCBW65	RCCBW80	RCCBW100



■ Polypropylene



**Individual
packing**

Excluded from 2014/68/EU Directive (art. 4, §3) - MIL-C-27487 & A-A-59326 - Fiberglass reinforced PP body - EPDM gasket - F304 cams - PS: 6 bar - TS: 0°C/+70°C.



Female adaptor A

DN	15	20	25	32	40	50	80	100
Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	3"	4"
code	2211004	2211005	2211006	2211007	2211008	2211009	2211011	2211012



Male coupling B

DN	15	20	25	32	40	50	80	100
Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	3"	4"
code	2212004	2212005	2212006	2212007	2212008	2212009	2212011	2212012



Hose coupling C

DN	15	20	25	32	40	50	80	100
Ø (mm)	20	25	32	40	50	63	90	110
code	2213004	2213005	2213006	2213007	2213008	2213009	2213011	2213012



Female coupling D

DN	15	20	25	32	40	50	80	100
Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	3"	4"
code	2214004	2214005	2214006	2214007	2214008	2214009	2214011	2214012



Hose adaptor E

DN	15	20	25	32	40	50	80	100
Ø (mm)	20	25	32	40	50	63	90	110
code	2215004	2215005	2215006	2215007	2215008	2215009	2215011	2215012



Male adaptor F

DN	15	20	25	32	40	50	80	100
Ø	1/2"	3/4"	1"	1"1/4	1"1/2	2"	3"	4"
code	2216004	2216005	2216006	2216007	2216008	2216009	2216011	2216012



Cap coupling DC

DN	15*	20*	25	32	40	50	80	100
code	2217005	2217005	2217006	2217007	2217008	2217009	2217011	2217012

* same product for DN15 & DN20.



Cap adaptor DP

DN	20	25	32	40	50	80	100	
code	-	2218005	2218006	2218007	2218008	2218009	2218011	2218012

Guillemin symmetrical couplings

■ Aluminium



Individual
packing

NF-EN 29572 - For irrigation, fire network, hydrocarbon & common fluids - Aluminium body - White NBR gasket - PS: 16 bar - TS: -10°C/+80°C.



2410 - Hose coupling

Ø	20/25	25/30	32/35	40/40	40/45	50/55	65/70	80/90	100/110	100/105	150/152
code	2410020	2410025	2410032	2410040	2410041	2410050	2410065	2410080	2410100	2410101	2410150



2411 - Hose coupling

Ø	50/51	65/63	80/76	80/81	100/102
code	2411050	2411065	2411080	2411081	2411100



2416 - Female coupling without lock

Ø	20	25	32	40	50	65	80	100
code	2416020	2416025	2416032	2416040	2416050	2416065	2416080	2416100



2415 - Male coupling without lock

Ø	20	25	32	40	50	65	80	100
code	2415020	2415025	2415032	2415040	2415050	2415065	2415080	2415100



2414 - Female coupling with lock

Ø	20	25	32	40	50	65	80	100	150
code	2414020	2414025	2414032	2414040	2414050	2414065	2414080	2414100	2414150



2413 - Male coupling with lock

Ø	20	25	32	40	50	65	80	100	150
code	2413020	2413025	2413032	2413040	2413050	2413065	2413080	2413100	2413150



2417 - Cap with lock

Ø	20	25	32	40	50	65	80	100	150
code	2417020	2417025	2417032	2417040	2417050	2417065	2417080	2417100	2417150



2412 - Reduced coupling with lock

Ø	40/20	40/25	40/32	50/25	50/32	50/40	65/40	65/50	80/40	80/50	80/65
code	2412040	2412041	2412042	2412050	2412051	2412053	2412065	2412066	2412080	2412081	2412082
Ø	100/40	100/50	100/65	100/80	150/100						
code	2412100	2412101	2412102	2412103	2412150						

■ Spare gaskets for Guillemin symmetrical couplings

WHITE EPDM

WHITE NBR

FKM

DN	20	25	32	40	50	65	80	100
code	9830837	9830830	9830831	9830832	9830833	9830834	9830835	9830836
code	9830820	9830821	9830822	9830823	9830824	9830825	9830826	9830827
code	9830847	9830840	9830841	9830842	9830843	9830844	9830845	9830846

■ Stainless steel CF8M



**Individual
packing**

NF-EN 29572 - For irrigation, fire network, hydrocarbon & common fluids - Stainless steel CF8M body - FKM gasket - PS: 16 bar - TS: -10°C/+180°C.



2420 - Hose coupling

Ø	20/25	25/30	32/35	40/45	50/55	65/70	80/90	100/110
code	2420020	2420025	2420032	2420040	2420050	2420065	2420080	2420100



2421 - Hose coupling

Ø	40/40	50/51	65/63	80/76	100/102
code	2421040	2421050	2421065	2421080	2421100



2426 - Female coupling without lock

Ø	20	25	32	40	50	65	80	100
code	2426020	2426025	2426032	2426040	2426050	2426065	2426080	2426100



2425 - Male coupling without lock

Ø	20	25	32	40	50	65	80	100
code	2425020	2425025	2425032	2425040	2425050	2425065	2425080	2425100



2424 - Female coupling with lock

Ø	20	25	32	40	50	65	80	100
code	2424020	2424025	2424032	2424040	2424050	2424065	2424080	2424100



2423 - Male coupling with lock

Ø	20	25	32	40	50	65	80	100
code	2423020	2423025	2423032	2423040	2423050	2423065	2423080	2423100



2428 - Welding with lock

Ø	15	20	25	32	40	50	65	80	100
code	2428015	2428020	2428025	2428032	2428040	2428050	2428065	2428080	2428100



2427 - Cap with lock

Ø	20	25	32	40	50	65	80	100
code	2427020	2427025	2427032	2427040	2427050	2427065	2427080	2427100



2429 - Cap without lock

Ø	25	32	40	50	65	80	100
code	2429025	2429032	2429040	2429050	2429065	2429080	2429100



2422 - Reduced coupling with lock

Ø	50/40	65/40	65/50	80/50	80/65	100/40	100/50	100/65	100/80
code	2422053	2422065	2422066	2422081	2422082	2422100	2422101	2422102	2422103



**Single spanner
wrench - steel**
(for DN20 to DN65)

code
9830897



**Universal spanner
wrench - steel**
(for DN20 to DN115)

code
9830898



Individual
packing

Excluded from 2014/68/EU Directive (art. 4, §3) - For water & compressed air - Distance between claws: 41 mm - NFE 29573 - Brass body -
⚠ Not compatible with DIN standard.

■ Brass - Without gasket

PS: 10 bar - TS: -5°C/+60°C.

2285 - Hose coupling

Ø	7	9	11	13	16	19	22	25
code	2285007	2285009	2285011	2285013	2285016	2285019	2285022	2285025

2286 - Male coupling

Ø	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"
code	2286002	2286003	2286004	2286005	2286006	2286007

2287 - Female coupling

Ø	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"
code	2287002	2287003	2287004	2287005	2287006	2287007

2288 - Cap coupling

for all references
code
2288001



Mandatory
packing applies

■ Brass - With NBR gasket

PS: 10 bar - TS: -5°C/+60°C.

2280 - Hose coupling

Ø	7	9	11	13	16	19	22	25
pack	10	10	10	10	10	10	10	10
code	2280007	2280009	2280011	2280013	2280016	2280019	2280022	2280025

2281 - Male coupling

Ø	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"
pack	10	10	10	10	10	10
code	2281002	2281003	2281004	2281005	2281006	2281007

2282 - Female coupling

Ø	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"
pack	10	10	10	10	10	10
code	2282002	2282003	2282004	2282005	2282006	2282007

Spare gasket Ø 22 - NBR

for all references
pack
code
9830984

Spare gasket Ø 16 (reduced hole) - NBR

for all references
pack
code
9830983

98440 - Claw clamp

Ref.	15	17	20	23	26	29	32	36	38
Ø ext.	14-16	16-18	19-21	22-24	25-27	28-30	31-33	34-37	37-39
Ø int.	7	9	10	11	13	16-19	19	22	25
code	9844015	9844017	9844020	9844023	9844026	9844029	9844032	9844036	9844038



Individual
packing

Excluded from 2014/68/EU Directive (art. 4, §3) - For all common fluids - Distance between claws: 41 mm - NFE 29573 - Stainless steel CF8M body -
⚠ Not compatible with DIN standard.

■ Stainless steel CF8M - With FKM gasket

PS: 10 bar - TS: -5°C/+150°C.

2290 - Hose coupling

Ø	16	19	25
code	2290016	2290019	2290025

2291 - Male coupling

Ø	1/2"	3/4"	1"
code	2291004	2291005	2291006

2292 - Female coupling

Ø	1/2"	3/4"	1"
code	2292004	2292005	2292006

2293 - Cap coupling

for all references
code
2293001

Spare gasket Ø 15 - FKM

for all references
code
9830986