




Series
DLD

Dual Channel Leak Detection Relay

Shaft Seal Leak Protection



Level

Series DLD Dual Channel Leak Detection Relay is used to monitor the shaft seals of two submersible pumps to detect a leak before pump failure. A leak is detected by sensing the status of a float or conductivity switch installed in the seal cavity. When this resistance drops below the set sensitivity, the output relay energizes and the corresponding LED indicator illuminates. The DLD offers normally open relay contacts to energize an alarm or de-energize the pump in the event of a leak. When the seal failure condition clears, the relay automatically resets. The DLD is available in two different adjustable sensitivities. All models utilize a 120 VAC control voltage. Installation is made simple with the standard 8-pin octal mount.

| Model | Sensitivity |
|---------|-------------------------------|
| DLD-ACY | 10 k to 25 k ohm adjustable |
| DLD-ACZ | 4.7 k to 100 k ohm adjustable |

SPECIFICATIONS

Power Requirement: 120 VAC, 50/60 Hz.

Power Consumption: 2 VA (approximate).

Isolation Voltage: 2500 V.

Temperature Limits:

Operating: -4 to 131°F (-20 to 55°C);

Storage: -40 to 185°F (-40 to 85°C).

Switch Type: (2) N.O. SPST.

Switch Voltage 9 VDC.

Electrical Rating: 5 A @ 120 VAC resistive, 345 VA inductive.

Response Times:

Energize: 6 ms (approximate);

Release: 2.5 ms (approximate).

Indicators: Respective red LED illuminates when leak is detected.

Enclosure: Polycarbonate dust cover.

Mounting: 8-pin octal.

Weight: 8 oz (227 g).

Agency Approvals: UL 508.