



## Models F222 & F451 Liquid/ Particle Filter s



### SPECIFICATIONS

**Filtration Efficiency:** 93% (removal of 0.01 micron particles).

**Maximum Pressure:** 150 psig (10 bar).

**Maximum Temperature:** 130°F (54°C).

**Max. Flow at 100 psig:** 22 scfm (F222); 45 scfm (F451).

**Inlet & Outlet Ports:** 1/4" female NPT.

**Mounting:** In-line only (F222); 1/4-20 mounting holes (F451).

### Materials of Construction:

Anodized Aluminum head, Polycarbonate bowl, cadmium plated steel tie rod, nylon internals, Buna-N seal.

**Weight:** 0.5 lb (0.2 kg) (F222); 1.1 lb (0.5 kg) (F451).

**Model F222** Liquid/Particle Filter

**Model 1201-2** Replacement Filters for F222 (pk of 3)

**Model F451** Liquid/Particle Filter

**Model 1201-3** Replacement Filters for F451 (pk of 3)

**Compressed air filters** protect equipment and instrumentation from harmful contaminants such as dirt, water and oil. Liquids are continuously coalesced and released through the manual drain valves. Replaceable filter element removes particles and droplets as small as 0.01 micron with 93% efficiency. Units have 1/4" female NPT inlet and outlet and manual drain valve.