




Series
CAM

Compressed Air Meter

Steady-State and Cumulative Totals PNP/4-20 mA Output



Flow



Dimensions

Model	A	B	C	E
CAM-10	10-53/64 [275.3]	18-45/64 [475.06]	2" NPT	Ø2-1/64 [Ø51.2]
CAM-20	8-9/32 [210.34]	11-13/16 [300.04]	1/2" NPT	Ø41/64 [Ø16.27]
CAM-30	14-49/64 [375.05]	18-45/64 [475.06]	1" NPT	Ø1-5/64 [Ø27.38]

The Series CAM Compressed Air Meter operates by the calorimetric measuring principle to detect the standard volume flow of operating compressed air. It is designed specifically to evaluate the current flow rate and the current consumed quantity in compressed air systems. With an easily programmable digital display, this unit offers a quick, accurate readout. The Series CAM is constructed of high-grade materials and is virtually maintenance free.

- Model CAM-10, 2" NPT, 1.4 - 412.0 SCFM
Model CAM-20, 1/2" NPT, 0.2 - 44.1 SCFM
Model CAM-30, 1" NPT, 1.0 - 132.4 SCFM

ACCESSORY
A-283, 4-Wire Connector

Class	Max. Oil Content	Max. Residual Dust		Max. Residual Water	
	Oil Content mg/m ³	Dust Concentration mg/m ³	Particle Size mg/µm	Residual Water g/m ³	Pressure Dew Point °C
1	0.01	0.1	0.1	0.003	-70
2	0.1	1	1	0.117	-40
3	1	5	5	0.880	-20
4	5	8	15	5.953	+3
5	25	10	40	7.732	+7
6	—	—	—	9.356	+10

SPECIFICATIONS
Service: Compressed air; Air quality (see chart).
Wetted Materials: Stainless Steel (304S15), ceramics, glass passivated, PEEK, polyester, Fluoroelastomer, anodized aluminum.
Accuracy: Class 1.4.1: ±3% of measured value +0.3% of full scale value. Class 3.4.4: ± 6% of measured value + .6% of full scale value.
Response Time: < 0.1 seconds.
Temperature Limit: 32 to 140°F (0 to 60°C).
Pressure Limit: 232 psig (16 bar).
Humidity Limit: 90% RH.
Power Requirements: 19-30 VDC.
Output Signal:
Output 1: PNP Open Collector: VOUT(max)=30 VDC / ISINK(max)=250mA
Output 2: 4-20 mA (scaleable) or PNP Open Collector.
Loop Resistance: 500 ohms.
Current Consumption: <100 mA.
Electrical Connections: 4 pin M12(Micro) Cable Connection.
Process Connections: 1/2", 1" and 2" NPT.
Display: 4-digit alpha numeric red LED.
Enclosure Rating: IP 65 (NEMA 4X).
Mounting Orientation: Vertical, Horizontal, Side with pipe length facing left.
Weight: CAM-10: 12.5 lb; CAM-20: 2.35 lb; CAM-30: 4.16 lb.
Agency Approvals: CE.